

DAKTRONICS SW-2108 PRODUCT SPECIFICATIONS

LANE	PLACE	TIME
1	8	15:12.63
2	6	15:01.39
3	5	14:56.24
4	2	14:48.17
5	1	14:47.80
6	3	14:50.76
7	4	14:52.31
8	7	15:03.02

This eight-line LED swimming scoreboard displays LANE and PLACE information along with TIME to 1/100 of a second. Both indoor and outdoor models are available. Scoreboard shown with alternating amber and red PanaView® digits.

DIMENSIONS	UNCRATED WEIGHT	POWER (120 VAC)
9'-11" H x 9'-0" W x 6" D (3.02 m, 2.74 m, 152 mm)	340 lb (154 kg)	800 Watts, 6.7 Amps

Note: Models with 240 VAC power at half the indicated amperage are also offered (International Use Only).

DIGITS & INDICATORS

- All digits are 10" (254 mm) high.
- Select all red, all amber or alternating rows of amber and red LED digits.
- Outdoor scoreboard features robust weather-sealed digits (see [DD2495646](#)).

CAPTIONS

- All captions are 5" (127 mm) high.
- Standard captions are vinyl, applied directly to changeable panels.

DISPLAY COLOR

Choose from 150+ colors (from Martin Senour® paint book) at no additional cost.

CONSTRUCTION

Durable, lightweight aluminum cabinet for excellent corrosion resistance

PRODUCT SAFETY APPROVAL

ETL listed, tested to CSA standards; CE approved

OPERATING TEMPERATURES

- Display: -22 to 122° Fahrenheit (-30 to 50° Celsius)
- Console: 32 to 130° Fahrenheit (0 to 54° Celsius)

DAKTRONICS SW-2108 PRODUCT SPECIFICATIONS

CONTROL CONSOLES	CONTROL OPTIONS
OmniSport® 2000 (see SL-05408)	Wired (standard): One-pair shielded cable of 22 AWG minimum is required. A cover plate with mounted connector and standard 2" x 4" x 2" (51 mm x 102 mm x 51 mm) outlet box is provided. Connector mates with signal cable from control console. Wireless (optional): 2.4 GHz spread spectrum radio features 64 non-interfering channels and 8 broadcast groups (see SL-04370).
Third-Party Control	Daktronics swimming scoreboards can be controlled by Colorado Time Systems® (CTS) controllers; Omega® Quantum, Ares 21 or OSM6 controllers (swim mode only); and Omega Scan'O'Vision™ or Finish Lynx® photo finish systems. Please specify when ordering.

GENERAL INFORMATION

100% solid state electronics are housed in an all aluminum cabinet. Scoreboard is shipped in five sections. Outdoor beam mounting hardware is provided; wall mounting hardware is not. Specifications and pricing are subject to change without notice.

OPTIONS & ACCESSORIES

- Multiple caption colors (see [DD2101644](#))
- Corner mounting kit (indoor model only)
- Advertising/identification panels
- Decorative accents
- Electronic message centers and video displays in multiple sizes

ADVERTISING/IDENTIFICATION PANELS

Backlit & Non-Backlit:

- 1'-2" H x 9'-0" W (356 mm, 2.74 m)
- 1'-9" H x 9'-0" W (533 mm, 2.74 m)
- 2'-4" H x 9'-0" W (711 mm, 2.74 m)

FOR ADDITIONAL INFORMATION

- Architectural Specifications: See [SL-05242](#)
- Manual: See [ED-12156](#)

WWW.DAKTRONICS.COM E-MAIL: SALES@DAKTRONICS.COM

OmniSport® and PanaView® are trademarks of Daktronics, Inc.
Martin Senour®, Colorado Time Systems®, Omega®, Scan'O'Vision™ and
FinishLynx® are registered trademarks of their owners.
SL-04195 110513 Page 2 of 2 Copyright © 2013 Daktronics, Inc.

