



### features.

- **Overall Height:** 4.50"
- **Overall Width:** 2.75"
- **Overall Depth:** 0.875"
- **Description:** Call switch for intercom systems—general purpose signaling and switching—includes 1-gang wall plate.
- **Switch:**
  - SPST (single pole, single throw) black rocker switch
  - Rating: 24VDC 500mA
  - Function: Momentary (normally open)
  - Connections: Screw terminal connections for easy field installation
- **Wall Plate:**
  - One-gang
  - Stainless steel
  - "PRESS TO OPEN" lettering
  - Mounting hardware
- **Optional:**
  - **#P1X Box:** One-gang surface-mount wall box measures 4.625"H x 2.875"W x 2.5"D. Box is 20-gauge steel with white finish. Features front flanged holes that conform to standard wall plate centers and hardware, and 0.5" rear/side knockouts.

### a&e specifications.

The call switch shall be Lowell #CS10, which shall be a single pole, single throw (SPST) momentary (normally open) black rocker switch. The switch rating shall be 24VDC 500mA. The switch shall be mounted in a one-gang wall plate with stainless steel finish. The plate shall feature black lettering stating "PRESS TO CALL". The unit shall feature screw terminals and include mounting hardware.

#### Optional

- The switch shall include a one-gang surface mount steel wall box with white finish, Lowell #P1X. The box shall measure 4.625"H x 2.875"W x 2.5"D. It shall feature side and rear knockouts.