



## C-5BM/5BM

### 5 BNC RGBHV Mini Coax Cable



Kramer's 5BM series cables are constructed of 5 mini coax cables in a single jacket with 75Ω BNC connectors at each end. They offer outstanding quality, durability, and high performance for any RGBHV video signal application.

#### FEATURES

- **Quality Construction** - Constructed from flexible, high quality 5 mini coax cable.
- **Applications** - Ideal for routing typical computer graphics video RGBHV signals to display devices such as projectors and monitors.
- **Easy Installation** - Breakout length is 0.5m (18in) on any cables 1.8m (6ft) or longer. Shorter cables have approx 0.18m (7in) breakout length.
- **Cable Specs** - For detailed cable specs, see Kramer BC-5X.
- **Varied Selection of Lengths** - Available in versions of 0.9 to 30.5m (3, 6, 10, 15, 25, 35, 50, 75 and 100ft).

| Model         | Description                  | Length Meter |       |
|---------------|------------------------------|--------------|-------|
| Male - Male   |                              |              |       |
| C-5BM/5BM-3   | 5 BNC (M) to 5 BNC (M) Cable | 3'           | 0.9M  |
| C-5BM/5BM-6   | 5 BNC (M) to 5 BNC (M) Cable | 6'           | 1.8M  |
| C-5BM/5BM-10  | 5 BNC (M) to 5 BNC (M) Cable | 10'          | 3.0M  |
| C-5BM/5BM-15  | 5 BNC (M) to 5 BNC (M) Cable | 15'          | 4.6M  |
| C-5BM/5BM-25  | 5 BNC (M) to 5 BNC (M) Cable | 25'          | 7.6M  |
| C-5BM/5BM-35  | 5 BNC (M) to 5 BNC (M) Cable | 35'          | 10.7M |
| C-5BM/5BM-50  | 5 BNC (M) to 5 BNC (M) Cable | 50'          | 15.2M |
| C-5BM/5BM-75  | 5 BNC (M) to 5 BNC (M) Cable | 75'          | 22.9M |
| C-5BM/5BM-100 | 5 BNC (M) to 5 BNC (M) Cable | 100'         | 30.5M |