





FEATURES


- High copper content and quality connectors for the best possible signal transfer
- Super Flex cable for installation ease
- Variety of configurations and lengths for most applications
- Cable types include:
 - RGB Component Video Cables
 - Composite Video Cables
 - Toslink Optical Cables
 - HDMI Cables, SVGA, Stereo RCA Patch, 3.5mm, & S-Video

RCI Custom Products completes the package by providing plates and panels, electronic solutions and professional products, and now... the means to connect it all together. Our **CA Series Cable Assemblies** are offered in different configurations and in different lengths, using high quality connectors and cable to optimize your installation. Perfect for Audio, Video and Data applications.


P/N	Description	
RGB/ Component w/Audio	Double Shielded, 100% EMI-RFI protection 24K gold-plated connectors	
CA502-72	RCA Assembly, R.G.B. w/ Audio pair, Ivory, 6 ft.	
CA502-144	RCA Assembly, R.G.B. w/ Audio pair, Ivory, 12 ft.	
CA502-300	RCA Assembly, R.G.B. w/ Audio pair, Ivory, 25 ft.	
CA502-600	RCA Assembly, R.G.B. w/ Audio pair, Ivory, 50 ft.	
RGB	Double Shielded, 100% EMI-RFI protection 24K gold-plated connectors	
CA500-72	RCA Assembly, R.B.G., Ivory 6 ft.	
CA500-144	RCA Assembly, R.B.G., Ivory 12 ft.	
CA500-300	RCA Assembly, R.B.G., Ivory 25 ft.	
CA500-600	RCA Assembly, R.B.G., Ivory 50 ft.	
Composite Video Cables	75 Ohm Impedance, Shielded, molded Nickel connectors	
CA559-36	BNC to BNC, RG59, Black, 3 ft.	
CA559-72	BNC to BNC, RG59, Black, 6 ft.	
CA559-144	BNC to BNC, RG59, Black, 12 ft.	
CA559-300	BNC to BNC, RG59, Black, 25 ft.	
CA559-600	BNC to BNC, RG59, Black, 50 ft.	
CA559-1200	BNC to BNC, RG59, Black, 100 ft.	
CA560-72	RCA to RCA, RG59, Black, 6 ft.	
Composite Video Cables	75 Ohm Impedance, Shielded, molded Nickel connectors	
CA560-144	RCA to RCA, RG59, Black, 12 ft.	
CA560-300	RCA to RCA, RG59, Black, 25 ft.	
Toslink Cables, Fiber Optic	Impervious to EMI-RFI interference, metal shell connectors	
CA601-36	Toslink Fiber Optic, 3 ft.	
CA601-60	Toslink Fiber Optic, 5 ft.	
CA601-120	Toslink Fiber Optic, 10 ft.	
CA601-180	Toslink Fiber Optic, 15 ft.	


HDMI Cables	Backward compatible with DVI signals, 75 Ohm Impedance	
CA570-1M	HDMI Cable, Black, 39"	
CA570-2 M	HDMI Cable, Black, 6.5 ft.	
CA570-3 M	HDMI Cable, Black, 9.75 ft.	
CA570-5 M	HDMI Cable, Black, 16.25 ft.	
CA580-7.5 M	HDMI High Performance Cable, Black, 24.4 ft.	
CA580-10 M	HDMI High Performance Cable, Black, 32.75 ft.	
CA580-15 M	HDMI High Performance Cable, Black, 49 ft.	
CA580-20 M	HDMI High Performance Cable, Black, 65.5 ft.	
CA580-25 M	HDMI High Performance Cable, Black, 82 ft.	


SVGA Male to Male	15 pin D-sub, UL 2919/2990, Ferrites Shield	
CA100M2M-36	SVGA Cable, Male/Male, Black 3 ft.	
CA100M2M-72	SVGA Cable, Male/Male, Black 6 ft.	
CA100M2M-120	SVGA Cable, Male/Male, Black 10 ft.	
CA100M2M-180	SVGA Cable, Male/Male, Black 15 ft.	
CA100M2M-300	SVGA Cable, Male/Male, Black 25 ft.	
CA100M2M-420	SVGA Cable, Male/Male, Black 35 ft.	
CA100M2M-600	SVGA Cable, Male/Male, Black 50 ft.	
CA100M2M-900	SVGA Cable, Male/Male, Black 75 ft.	
CA100M2M-1200	SVGA Cable, Male/Male, Black 100 ft.	

SVGA Male/Female	15 pin D-sub, UL 2919/2990, Ferrites Shield	
CA100M2F-36	SVGA Cable, Male/Female, Black, 3 ft.	
CA100M2F-72	SVGA Cable, Male/Female, Black, 6 ft.	
CA100M2F-120	SVGA Cable, Male/Female, Black, 10 ft.	
CA100M2F-180	SVGA Cable, Male/Female, Black, 15 ft.	
CA100M2F-300	SVGA Cable, Male/Female, Black, 25 ft.	
CA100M2F-420	SVGA Cable, Male/Female, Black, 35 ft.	
CA100M2F-600	SVGA Cable, Male/Female, Black, 50 ft.	
CA100M2F-900	SVGA Cable, Male/Female, Black, 75 ft.	
CA100M2F-1200	SVGA Cable, Male/Female, Black, 100 ft.	

SVGA Male w/ 3.5mm Stereo	15 pin D-sub, 4-Contact Mini-DIN Plug Gold Plated	
CA101M2M-36	SVGA Cable, Male w/ 3.5mm Stereo, Black, 3 ft.	
CA101M2M-72	SVGA Cable, Male w/ 3.5mm Stereo, Black, 6 ft.	
CA101M2M-120	SVGA Cable, Male w/ 3.5mm Stereo, Black, 10 ft.	
CA101M2M-300	SVGA Cable, Male w/ 3.5mm Stereo, Black, 25 ft.	
CA101M2M-600	SVGA Cable, Male w/ 3.5mm Stereo, Black, 50 ft.	

SVGA to BNC Tails	HD15 Female to 5 BNC	
TTL15FFBF-04	SVGA Female to 5 BNC Females (7")	
TTLFBM-03	SVGA Female to 5 BNC Males (9")	

L/R Stereo Audio Patch Cables, RCA/RCA	Gold-plated connectors, Stranded center conductors.	
CA200M2M-36	Stereo Audio Patch Cables, L/R (Red/White), 3 ft.	
CA200M2M-72	Stereo Audio Patch Cables, L/R (Red/White), 6 ft.	
CA200M2M-144	Stereo Audio Patch Cables, L/R (Red/White), 12 ft.	
CA200M2M-300	Stereo Audio Patch Cables, L/R (Red/White), 25 ft.	


L/R Stereo Audio + Video Patch Cables RCA/RCA	Gold-plated connectors, Stranded center conductors.	
CA202M2M-36	Stereo Audio + Video Patch Cables (Red/White/Yellow) 3 ft.	
CA202M2M-72	Stereo Audio + Video Patch Cables (Red/White/Yellow) 6 ft.	
CA202M2M-144	Stereo Audio + Video Patch Cables (Red/White/Yellow) 12 ft.	
CA202M2M-216	Stereo Audio + Video Patch Cables (Red/White/Yellow) 18 ft.	
CA202M2M-240	Stereo Audio + Video Patch Cables (Red/White/Yellow) 20 ft.	
CA202M2M-300	Stereo Audio + Video Patch Cables (Red/White/Yellow) 25 ft.	
CA202M2M-600	Stereo Audio + Video Patch Cables (Red/White/Yellow) 50 ft.	






www.rcicustom.com

CA Series Cable Assemblies

CA901-1

L/R Stereo Audio + S-Video Patch Cables	Gold-plated connectors, 4-Contact Mini-DIN Plug	
CA205M2M-72	Stereo Audio RCA Male + S-Video Male Patch Cable, 6 ft.	
CA205M2M-144	Stereo Audio RCA Male + S-Video Male Patch Cable, 12 ft.	
CA205M2M-300	Stereo Audio RCA Male + S-Video Male Patch Cable, 25 ft.	

3.5mm Stereo Audio Patch Cables	Nickel-plated connectors Low-Loss Copper Shield	
CA300M2M-72	3.5mm Stereo Cable, Male/Male, 6 ft.	
CA300M2M-144	3.5mm Stereo Cable, Male/Male, 12 ft.	
CA300M2M-300	3.5mm Stereo Cable, Male/Male, 25 ft.	
CA300M2F-72	3.5mm Stereo Cable, Male/Female, 6 ft.	
CA300M2F-144	3.5mm Stereo Cable, Male/Female, 12 ft.	
CA300M2F-300	3.5mm Stereo Cable, Male/Female, 25 ft.	

S-Video Cables	Low-Loss Shielded, 4-Contact Mini-DIN Plug Gold Plated	
CA400M2M-36	S-Video Cable, Male/Male, 3 ft.	
CA400M2M-72	S-Video Cable, Male/Male, 6 ft.	
CA400M2M-144	S-Video Cable, Male/Male, 12 ft.	
CA400M2M-300	S-Video Cable, Male/Male, 25 ft.	
CA400M2M-600	S-Video Cable, Male/Male, 50 ft.	
CA400M2M-900	S-Video Cable, Male/Male, 75 ft.	
CA400M2M-1200	S-Video Cable, Male/Male, 100 ft.	

A & E SPECIFICATIONS

Interconnecting cables shall be the RCI Custom Products CA Series Cable Assemblies. Cables shall maintain high copper content conductors and 24 kt. Gold-plated or Nickel plated connectors. Specify RCICA502-____ (72, 144, 300, 600) for RGB Component video cables with Audio pair that are 100% double shielded against EMI-RFI, RCICA500-____ (72, 144, 300, 600) for RGB Component video cables that are 100% double shielded against EMI-RFI, RCICA____-____ (559-36, 559-72, 559-144, 559-300, 559-600, 559-1200, 560-72, 560-144, 560-300) for Composite video cables that are 75 ohms, shielded with molded nickel plated connectors, RCICA601-____ (36, 60, 120, 180) for Toslink Fiber Optic cables that are EMI-RFI shielded, RCICA____-____ (570-1M, 570-2M, 570-3M, 570-5M, 580-7.5M, 580-10M, 580-15M, 580-20M, 580-25M) for High Performance HDMI cables that are 75 ohms and backward compatible with DVI signals, RCICA100M2M-____ (36, 72, 120, 180, 300, 420, 600, 900, 1200) for SVGA with male to male connectors, RCICA100M2F____ (36, 72, 120, 180, 300, 420, 600, 900, 1200) for SVGA with Male to Female connectors, RCICA101M2M-____ (36, 72, 120, 300, 600) for SVGA Male to 3.5mm Male, RCICA200M2M-____ (36, 72, 144, 300) for L/R Stereo RCA male to RCA Male patch cables, RCICA202M2M-____ (36, 72, 144, 216, 240, 300, 600) for L/R Stereo and Video RCA male to male patch cables, RCICA205M2M-____ (L/R Stereo RCA male to S-video male, RCICA300M2M-____ (72, 144, 300) for 3.5mm Stereo male to male, RCICA300M2F-____ (72, 144, 300) for 3.5mm Stereo male to female, or RCICA400M2M-____ (36, 72, 144, 300, 600, 900, 1200) for S-Video male to male cables..