

# CEN-GWEXER

## infiNET EX® & ER Wireless Gateway

The CEN-GWEXER is a 2-way RF wireless transceiver designed for use with Crestron® infiNET EX® and “ER” (Extended Range RF) wireless devices. A single CEN-GWEXER gateway enables an entire wireless network of Crestron remotes, keypads, lighting dimmers, motorized shades, thermostats, door locks, and other devices to communicate with a Crestron control system.

### infiNET EX® Technology

Ultra-reliable infiNET EX wireless technology provides steadfast 2-way RF communications throughout a residential or commercial structure without the need for physical control wiring. Employing a 2.4 GHz mesh network topology, nearly every infiNET EX device on the network acts as an “expander,” relaying wireless commands between the gateway and all the other “EX” devices on the network to ensure that every command reaches its intended destination without disruption. Each infiNET EX device that is added to the network effectively increases the range and stability of the entire network by providing multiple redundant signal paths. The wireless range between any two EX devices is typically up to 150 ft (46 m) indoors.[1]

### “ER” Extended Range RF Technology

Crestron Extended Range (ER) wireless technology enables compatibility with certain Crestron wireless touch screens and handheld remotes including the **TSR-302**, **TST-600**, **TST-602**, and **TST-902**. [2] Crestron “ER” operates in the same 2.4 GHz spectrum as infiNET EX, and is specifically optimized for use with wireless touch screen devices to ensure robust and dependable bidirectional RF communications. The CEN-GWEXER continuously monitors each ER device on the network, diligently keeping track when a device goes to sleep, shuts down, or wanders out of range, and restores communications seamlessly when the device reappears on the network. The typical wireless range for ER devices is 100 to 200 feet indoors, or up to 1000 feet outdoors. For even greater coverage, ER supports roaming amongst up to eight gateways. [3]

### Easy Setup

The CEN-GWEXER can manage both infiNET EX and ER wireless devices simultaneously, eliminating the need for separate gateways, antennas, and LAN connections. Setting up a network of infiNET EX and/or ER devices is simple, utilizing dynamic discovery to locate and acquire each wireless device automatically. If no ER devices are acquired, the CEN-GWEXER can support up to 100 infiNET EX devices (inclusive of up to six Crestron **MLX-3** and/or **MTX-3** handheld remotes). Each ER device that is added to the network negates ten EX devices, with a maximum of ten ER devices allowed. For a more detailed breakdown, please refer to “Supported Devices” in the specifications section of this spec sheet. [4]

### Single-Wire Hookup

NO PHOTO AVAILABLE

- Crestron offers the **PWE-4803RU** PoE Injector, which connects inline with the Ethernet cable, allowing for installation at any convenient location between the gateway and the network switch. The PWE-4803RU is capable of powering a single gateway, and is available separately or packaged with the gateway as model CEN-GWEXER-PWE or CENI-GWEXER-PWE.
- Crestron also offers Ethernet switches with built-in PoE (models **CEN-SW-POE-5** and **CEN-SWPOE-16** [5]), affording a complete high-performance networking solution capable of providing PoE for multiple gateways and other PoE devices. Using an Ethernet switch with built-in PoE eliminates the need for individual PoE Injectors.

As an alternative to PoE, the CEN-GWEXER can be powered using an optional 24VDC power pack, model **PW-2420RU**. [5]

### Integrator Friendly Enclosure

The CEN-GWEXER features the Crestron IFE form factor, a compact “Integrator Friendly Enclosure” design that fits almost anywhere and enables a variety of installation options. Its shape allows multiple gateways and other IFE compliant devices to be stacked together. Using the included mounting bracket, it can be fastened to any flat surface or snapped onto a standard DIN rail. Rack mount and pole mount kits are also available. [5]

> *Multipurpose 2-way RF wireless gateway*  
> *Simultaneously supports infiNET EX® and Crestron “ER” wireless devices [2]*

# CEN-GWEXERinfiNET EX® & ER Wireless Gateway

- > "Extended Range" RF technology optimized for wireless touch screen remotes
- > Dynamic discovery for fast, easy setup
- > "Wi-Fi@ friendly" channel selection for *trouble-free operation*
- > Built-in RF network diagnostics
- > Up to 150 feet (46 meters) infiNET EX range indoors, 250 feet (76 m) outdoors [1]
- > 100 to 200 feet (33 to 66 meters) ER range indoors, 1000 feet outdoors
- > Supports infiNET EX expanders and ER roaming for extended *coverage [1,3]*
- > Extendable antenna using optional ANT-EXT [5]
- > Compact, stackable "IFE small" form factor
- > Surface or DIN rail mountable using bracket provided
- > Available rack mount and pole mount options [5]
- > High-speed Ethernet control system interface
- > 24VDC or PoE network powered
- > Models available with PoE injector included
- > Optional 24VDC power pack sold separately

## SPECIFICATIONS

### Supported Devices

**infiNET EX® Devices:** Supports all Crestron and third-party infiNET EX devices including **HR-100**, **HR-150**, **MLX-3**, and **MTX-3** handheld remotes  
**infiNET EX Expanders:** Supports Crestron infiNET EX expander models **CLW-EXPEX** and **GLA-EXPEX**

**ER "Extended Range" Devices:** Supports Crestron wireless touch screen models **TSR-302**, **TST-600**, **TST-602**, and **TST-902** [2]

Maximum Devices Allowed [4]:

**infiNET EX Devices\*infiNET EX ExpandersER "Extended Range" Devices**

10050  
9051  
8052  
7053  
6054  
5055  
4056  
3057  
2058  
1059  
0510

\*Inclusive of a maximum of six MLX-3 and/or MTX-3 remotes

### Wireless Communications

**RF Transceiver:** infiNET EX & ER 2-way RF, 2.4 GHz ISM Channels 11-26 (2400 to 2483.5 MHz), default channel 15; IEEE 802.15.4 compliant

**Transmit Power:** +20 dBm (models CEN-GWEXER & CEN-GWEXER-PWE); +8 dBm (International models CENI-GWEXER & CENI-GWEXER-PWE)

**infiNET EX Range (typical):** 150 ft (46 m) indoor, 250 ft (76 m) outdoor, to nearest mesh network device(s); subject to site-specific conditions and individual device capabilities [1]

**ER Range (typical):** 100 to 200 ft (33 to 66 m) maximum indoor, 1000 ft (305 m) outdoor, subject to site-specific conditions

**ER Roaming:** Supports roaming amongst up to 8 gateways [3]

### Wired Communications

**Ethernet:** 10/100 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP, IEEE 802.3af and 802.3at Type 1 compliant

### Controls & Indicators

**PWR:** (1) Green LED, indicates operating power supplied via PoE or 24VDC

**ACT:** (1) Red LED, indicates wireless RX and TX data activity

**ACQUIRE:** (1) Recessed pushbutton with red LED, used to set up connections with wireless devices

**SETUP:** (1) Recessed pushbutton with red LED, used to set up connection with the control system via Ethernet

**RESET:** (1) Recessed pushbutton, for hardware reset

**LAN PoE:** (1) Green and (1) Amber LEDs, green indicates Ethernet link status, amber indicates Ethernet activity

### Connectors

**ANTENNA:** (1) Connection for supplied antenna

**COMPUTER:** (1) Micro-B USB female;

Computer console port, for installer use only;

6 ft (2.83 m) Micro-B to A USB cable included

**G:** (1) 4-40 screw, chassis ground lug

**24VDC 0.75A:** (1) 2.1 x 5.5 mm DC power connector;

24 Volt DC power input;

**PW-2420RU** power pack sold separately

**LAN PoE:** (1) 8-pin RJ45, female;

10Base-T/100Base-TX Ethernet port;

Power over Ethernet compliant

### Power Requirements

**Power over Ethernet:** IEEE 802.3at Type 1 (802.3af compatible) Class 1 (3.84 W) PoE Powered Device;

100-250 Volts AC, 50/60 Hz PoE Injector, model **PWE-4803RU** included with models CEN-GWEXER-PWE & CENI-GWEXER-PWE

**Power Pack:** 0.75 Amps @ 24 Volts DC;

100-240 Volts AC, 50/60 Hz power pack, model **PW-2420RU** sold separately

Note: May be powered via PoE or power pack, not both.

**Power Consumption:** 2.1 Watts typical

### Environmental

**Temperature:** 41° to 113° F (5° to 45° C)

**Humidity:** 10% to 90% RH (non-condensing)

**Heat Dissipation:** 7 BTU/Hr

### Construction

**Enclosure:** IFE small form factor, black and blue plastic

**Mounting:** Freestanding, stackable, surface mount, or 35 mm DIN EN 60715 rail mount; occupies 8 DIN module spaces (144 mm); surface/DIN rail mounting bracket included, optional rack mount and pole mount kits sold separately

### Dimensions

(Without antenna)

**Height:** 1.35 in (35 mm);

1.77 in (45 mm) with bracket

**Width:** 5.04 in (128 mm);

5.36 in (137 mm) with bracket

**Depth:** 5.20 in (133 mm)

### Weight

TBA

### Available Models

**CEN-GWEXER:** infiNET EX® & ER Wireless Gateway [Available March, 2016]

**CEN-GWEXER-PWE:** infiNET EX® & ER Wireless Gateway w/PoE Injector [Available March, 2016]

**CENI-GWEXER:** infiNET EX® & ER Wireless Gateway – International Version [Available March, 2016]

**CENI-GWEXER-PWE:** infiNET EX® & ER Wireless Gateway w/PoE Injector – International Version [Available March, 2016]

# CEN-GWEXERinfiNET EX® & ER Wireless Gateway

**PWE-4803RU:** PoE Injector, universal 100-250 Volts AC [Included Quantity for CEN-GWEXER-PWE, CENI-GWEXER-PWE

## Available Accessories

**ANT-EXT-10:** 10 ft Antenna Extender for CEN-HPRFGW, CEN-RFGW-EX, CEN-WAP-ABG-1G, & MC3

**RMK-IFE-1U:** IFE Rack Mount Kit

**PLMK-IFE-101:** IFE Pole Mount Kit

**CLW-EXPEX-GD-W-T:** infiNET EX® Wireless Expander, Ground Pin Down, White Textured

**GLA-EXPEX:** Crestron Green Light® Wireless Expander for infiNET EX® Networks

**PWE-4803RU:** PoE Injector, universal 100-250 Volts AC

**CEN-SW-POE-5:** 5-Port PoE Switch

**CEN-SWPOE-16:** 16-Port Managed PoE Switch

**PW-2420RU:** Desktop Power Pack, 24VDC, 2A (50 Watts), 2.1mm, Universal

## Notes:

1. Battery-powered infiNET EX devices do not provide expander functionality, and may have reduced RF range capabilities. Consult the specifications for each network device to confirm its actual wireless capabilities. Crestron also offers dedicated infiNET EX expanders (models **CLW-EXPEX** or **GLA-EXPEX**, sold separately), which may be deployed to fill gaps in coverage and extend the wireless range of the mesh network. infiNET EX expanders are only for infiNET EX networks and offer no benefit to the performance of ER devices. A maximum of five infiNET EX expanders may be deployed on an infiNET EX network.
2. The CEN-GWEXER is not compatible with **TPS-6X** or **UFO-WPR-3ER** model remotes. For these devices, please use the dedicated ER gateway model **CEN-ERFGW-POE**.
3. Roaming capability using multiple gateways is for ER devices only. infiNET EX utilizes only one gateway and does not support roaming.
4. Best practices suggest configuring the system with no more than 50% of the maximum devices allowed per gateway. Additional gateways may be deployed to support more devices, with a maximum of 16 gateways permitted on a complete system (RF conditions allowing).
5. Item(s) sold separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at:

[patents.crestron.com](http://patents.crestron.com).

Certain Crestron products contain open source software. For specific information, please visit [www.crestron.com/opensource](http://www.crestron.com/opensource).

Crestron, the Crestron logo, Crestron Green Light, and infiNET EX are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Wi-Fi is either a trademark or registered trademark of Wi-Fi Alliance in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2015 Crestron Electronics, Inc.