ClearOne

Users looking for a complete small-room and executive office video collaboration solution can find everything they need in the COLLABORATE Live 300 system.

Featuring the same simple and friendly user interface found in larger room systems, COLLABORATE Live 300 includes wireless presentation and interactive whiteboard capabilities along with everything needed for high quality audio and video collaboration.

APPLICATIONS

Video Conferencing

Audio Conferencing

Cloud Video Collaboration

Wireless Presentation

Whiteboard

Small Meeting Rooms

Executive Offices

Key Highlights

+ User interface as intuitive and simple as familiar mobile and tablet dervices

+ SIP/H.323 video conferencing

+ Skype® for Business client

+ Wireless presentation and interactive whiteboard

CHAT 150C Speakerphone

+ HDConference™ audio processing

+ Distributed Echo Cancellation®

+ Adaptive modelling with acoustic intelligence

+ Three microphones with 360° pickup

+ First mic priority intelligence

UNITE 150 PTZ camera

+ Full HD 1080p30

+ 12x optical zoom

+ 73° wide-angle

+ Backlight compensation

COLLABORATE Space

+ Complimentary 90-day trial of COLLABORATE Space, our powerful cloud-based audio and video conferencing application

COLLABORATE Live 300 Codec Appliance

UNITE 150
PTZ Camera

CHAT 150C Speakerphone

COLLABORATE Space conferencing application (90 days)

Note: Components not shown to scale.

PRODUCT SPECIFICATIONS

COLLABORATE Live 300

COLLABORATE Live 300 codec appliance
UNITE 150 PTZ Camera
CHAT 150C Speakerphone
Power supplies, cables and accessories
COLLABORATE Space conferencing application
  (90 days)
One-year support and maintenance with warranty

COLLABORATE Live 300 Codec Appliance

Video input: 1x USB 3.0
Video output: 1x HDMI, 1x Display port
Audio input: USB (Digital audio)
Audio output: USB, S/PDIF
USB: 4x USB 3.0

UNITE 150 Camera

Full HD 1080p30
73° wide-angle view
USB 3.0/2.0, Line In
Remote control, USB (UVC), RS-232
±170° pan, -30° to +90° tilt, 12x optical zoom

CHAT 150C Speakerphone

ClearOne HDConference™ audio processing
Three-built-in-microphone array with 360° pickup
Attach option to daisy-chain another CHAT 150
Large loudspeaker with Max Output Level: 85 dB
SPL @ 1 meter
Wideband audio frequency response (20Hz-20kHz)

Video Characteristics

Resolution up to 1080p @ 30 fps (Rx)
H.261, H.263, H.263+/++
H.264/AVC High Profile – up to 6Mbps
H.264/SVC (Skype for Business)

Audio Standards

20KHz: AAC-LD
14KHz: G.722.1 Annex C
7KHz: G.722, G.722.1
3.4KHz: G.711, G.723.1, G.728. G.729. AMR (3G)

Data Characteristics

H.239 support for data sharing
Resolution up to 1080p
Data inputs via wireless, datapoint (HDMI-to-USB adapter)

Control

Web-based management and control
Telnet API for 3rd-party control
AMX and Crestron modules

Part Number

930-3001-302