



DE250

HF Drivers FE - 1.0 Inches

120 W continuous program power capacity
 1' horn throat diameter
 44 mm (1.7 in) aluminium voice coil
 Polyimide diaphragm
 1000 - 18000 Hz response
 108.5 dB sensitivity

Specifications

Throat diameter	25 mm (1.0 in)
Nominal impedance	8 Ω
Minimum impedance	7.8 Ω
Nominal power handling	60 W
Continuous power handling	120 W
Sensitivity (1W/1m)	108.5 dB
Frequency range	1 - 18 kHz
Recommended crossover	1.6 kHz
Voice coil diameter	44 mm (1.7 in)
Winding material	Aluminium
Inductance	0.11 mH
Diaphragm material	Polyimide
Flux density	1.85 T
Magnet material	Ceramic

Mounting And Shipping Info

Overall diameter	120 mm (4.7 in)
Depth	62 mm (2.4 in)
Net weight	2.1 kg (4.6 lb)
Shipping units	8
Shipping weight	17.5 kg (38.5 lb)
Shipping box	260x260x190 mm (10.2x10.2x7.5 in)

Other

Replacement diaphragm	MMDE2508
-----------------------	----------

Mounting And Shipping Info

Two M6 holes 180° on 76 mm (3 in) diameter
Three M6 holes 120° on 57 mm (2.2 in) diameter