

EB-670

DATASHEET / BROCHURE



Liven up the classroom and deliver a screen size of up to 93 inches, utilising 3LCD technology, to display educational content.

With a brightness of 3,100 lumens and XGA resolution, the EB-670's ultra-short-throw design allows you to present large images from a very short distance with minimised shadows and glare. A 14,000:1 contrast ratio and HDMI input mean that students benefit from sharp, clear images.

Quality image

Epson's 3LCD technology ensures high-quality images with equally high White and Colour Light Output for vivid colours and bright images, even in daylight, and three times brighter colours than competitive projectors¹.

Keep costs down

Project for longer with improved reliability and a longer lamp life of up to 10,000 hours in eco mode.

Enhanced learning

Split-screen functionality allows two pieces of content to be displayed simultaneously without compromising on quality. The moderator function allows teachers to remain in control, choosing what content to display.

Optional wireless capability

Wirelessly display content easily from a range of smart devices and Google Chromebooks using our iProjection App².

Document camera compatibility

Connecting the optional Epson document camera allows you to easily display images and 3D objects with incredible detail for the whole class to see.

KEY FEATURES

- **Up to 93-inch display and outstanding quality**
XGA resolution with Epson 3LCD technology
- **Reliable**
Improved reliability and a longer lamp life
- **Wireless Connectivity (Optional)**
Allows content to be shown from a range of devices
- **Long lamp life**
Up to 10,000 hours in eco mode
- **Ultra short throw projection**
For maximum installation flexibility



EPSON
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System	3LCD Technology
LCD Panel	0.55 inch with D9

IMAGE

Color Light Output	3,100 Lumen- 1,800 Lumen (economy) In accordance with ISO 21118:2013
White Light Output	3,100 Lumen - 1,800 Lumen (economy) In accordance with ISO 21118:2013
Resolution	XGA, 1024 x 768, 4:3
Aspect Ratio	4:3
Contrast Ratio	14,000 : 1
Light source	Lamp
Lamp	215 W, 5,000 h durability, 10,000 h durability (economy mode)
Keystone Correction	Manual vertical: $\pm 3^\circ$, Manual horizontal $\pm 3^\circ$
Colour Video Processing	10 Bits
2D Vertical Refresh Rate	100 Hz - 120 Hz
Colour Reproduction	Upto 1.07 billion colours

OPTICAL

Throw Ratio	0.32 - 0.43:1
Zoom	Digital, Factor: 1 - 1.35
Lens	Optical
Screen Size	55 inches - 93 inches
Projection Distance Wide	0.4 m (56 inch screen)
Projection Distance Tele	0.6 m (93 inch screen)
Projection Lens Focal Length	3.7 mm
Projection Lens Focus	Manual
Offset	7 : 1

CONNECTIVITY

USB Display Function	3 in 1: Image / Mouse / Sound
Interfaces	USB 2.0 Type A, USB 2.0 Type B, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11b/g/n (optional), VGA in (2x), VGA out, HDMI in (3x), Composite in, RGB in (2x), RGB out, MHL, Stereo mini jack audio out, Stereo mini jack audio in (3x), Microphone input
Epson iProjection App	Ad-Hoc / Infrastructure

ADVANCED FEATURES

Security	Kensington lock, Control panel lock, Password lock, Padlock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection
2D Colour Modes	Dynamic, Cinema, Presentation, sRGB, Blackboard
Other features	AV Mute Slide, Auto brightness adjustment, Automatic input selection, Built-in speaker, CEC compatible, Customizable user logo, Digital zoom, Direct Power on/off, Document Camera Compatible, Dynamic lamp control, Easy OSD pre-setting, Home Screen, Long lamp life, Split-Screen-Function, Wireless LAN capable
Interactivity	No
Video Color Modes	Blackboard, Dynamic, Presentation, Sports, sRGB, Theatre, Whiteboard
Projector control	via: AMX, Crestron, Control4

EB-670

WHAT'S IN THE BOX

- Main unit
- Power cable
- Remote control incl. batteries
- User manual (CD)
- Warranty card
- Wall hanging bracket
- Quick Start Guide



EPSON
WORLD LEADER
IN PROJECTORS

Source: Futuresource Consulting Ltd.

EPSON[®]
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

EB-670

GENERAL

Power consumption	317 Watt, 230 Watt (economy)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	367 x 400 x 149 mm (Width x Depth x Height)
Product weight	5.7 kg
Noise Level	Normal: 35 dB (A) - Economy: 28 dB (A)
Supported Temperature	Operation 5° C - 40° C, Storage -10° C - 60° C
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%
	<p>If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could break and cause the projector to drop from the ceiling.</p> <p>If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance.</p>
Included Software	EasyMP Monitor, iProjection
Options	Air filter ELPAF38, Connection and control box, Document camera, External Speaker, Quick wireless USB key, USB extension cable
Compatible Operating Systems	Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Ubuntu 14.10, Ubuntu 15.04, Ubuntu 15.10, Ubuntu 16.04 LTS, Windows 10, Windows 8, Windows 8.1
Loudspeaker	16 Watt
Room Type / Application	Meeting room / Classroom
Positioning	Wall Mounted
Colour	White / Grey
TCO Certified	For further information relating to TCO Certified please visit https://tcocertified.com/files/certification/Information-document-for-end-users.pdf

OTHER

Warranty	60 months Carry in or 8,000 h, Lamp: 60 months or 1,000 h Optional warranty extension available
----------	--

OPTIONAL ACCESSORIES

- Active Speakers (2 x 15W) - ELPSP02
V12H467040DA
- Active Speakers (2 x 15W) - ELPSP02
V12H467040
- Control and Connection Box - ELPCB02
V12H614040
- Wireless LAN Adapter - ELPAP10
V12H731P01
- ELPPLP90
V13H010L90
- Air Filter - ELPAF49
V13H134A49
- Table Mount for Ultra-short-throw Series - ELPMB29
V12H516040

EB-670

LOGISTICS INFORMATION

SKU	V11H747040 V11H747041
EAN code	8715946605272
Country of Origin	Philippines
Layer	2 Units



* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com
Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04
(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742
Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00
Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 465-9621
Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal – 0,99 kr/min, Lokala samtal – 0,30 kr/min, Utlandssamtal – 0,89 kr/min)
Switzerland 022 592 7923
Turkey (0212) 3360303 United Kingdom 0871 222 6702

1. - Colour Brightness (Colour Light Output) measured in accordance with IDMS 15.4. Colour Brightness will vary depending on usage conditions. Leading Epson 3LCD business and education projectors compared to leading one-chip DLP projectors, based on NPD data for June 2013 through May 2014 and PMA Research data for Q1 through Q3 2013. For more information please visit www.epson.eu/CLO
2. - iProjection App available on Android and iOS devices, and Google Chromebooks.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

EPSON[®]