




VS-1616D

2x2 to 16x16 Modular Multi-Format Digital Matrix Switcher



The VS-1616D is a high-performance matrix switcher chassis for DVI & HDMI signals. The unit is modular and populated from 2x2 to 16x16 in increments of two inputs and/or two outputs. The chassis includes a power supply, control module and a test module that can monitor and test any input and output in the matrix.

FEATURES

- **Kramer Core™ - FLEXIBLE INFRASTRUCTURE CONVERSION!** Copper, Fiber or Twisted Pair – all can be used at the same time, according to input/output module selection. The matrix receives digital signals from compatible Kramer transmitters, automatically converts between available infrastructure options and sends the signals to compatible Kramer receivers. Kramer Core™ solution is the ultimate in versatility!
- **Max. Data Rate - 9.6Gbps (3.2Gbps per graphic channel)** depending on the cards used.
- **HDTV Compatible.**
- **HDCP Compliant -** With DVI (HDCP) and HDMI modules.
- **HDMI Support -** HDMI Compressed Audio Channels.
- **DGKat™ Signal Integration -** Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables. We strongly recommend using Kramer DGKat™ cables designed specifically for optimum performance.
- **Kramer Equalization & re-Klocking™ Technology -** Rebuilds the digital signal to travel longer distances.
- **Modular & Easily Configurable Platform -** Input or output module types can be mixed and added in increments of 2 from 2x2 up to 16x16.
- **Available Modules -** DVI, DVI (HDCP), DVI (dual link), HDMI, LC optical & DGKat twisted pair.
- **I-EDIDPro™ Kramer Intelligent EDID Processing™ -** Intelligent EDID handling & processing algorithm ensures Plug and Play operation for DVI and HDMI systems.
- **Flexible Control Options -** Front panel, IR remote, RS-232 (K-Router™ Windows®-based software is included), Ethernet.
- **Front Panel Lockout.**
- **Take Button -** Executes multiple switches all at once.
- **Memory Locations -** Stores multiple switches as presets to be recalled and executed as needed.

- Test Pattern Module - With 4 output resolutions for troubleshooting video problems.
- Worldwide Power Supply - 100–240V AC.
- Standard 19" Rack Mount Size - 4U. Rack "ears" included.



www.kramerelectronics.com

VS-1616D

TECHNICAL SPECIFICATIONS

| | |
|------------------------|---|
| INPUTS: | 2 to 16 (in increments of 2) of the following inputs: DVI or HDCP, 1.2Vpp on DVI Molex 24-pin (F) connectors; DDC signal 5Vpp (TTL); HDMI; fiber optic on LC connectors; DGKat on RJ-45 connectors; 1 to 8 (in increments of 1) DVI dual link, 1.2Vpp on DVI Molex 24-pin (F) connectors. |
| OUTPUTS: | 2 to 16 (in increments of 2) of the following outputs: DVI or HDCP, 1.2Vpp on DVI Molex 24-pin (F) connectors; DDC signal 5Vpp (TTL); HDMI; fiber optic on LC connectors; DGKat on RJ-45 connectors; 1 to 8 (in increments of 1) DVI dual link, 1.2Vpp on DVI Molex 24-pin (F) connectors. |
| MAX. DATA RATE: | 9.6Gbps (3.2Gbps per graphic channel) depending on the cards used. |
| MAX RESOLUTION: | Up to UXGA; 1080p, 1920x1200. |
| CONTROLS: | Front panel buttons, infrared remote control transmitter, RS-232, Ethernet. |
| SWITCHING: | Confirm or At Once for immediate switching. |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F). |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F). |
| HUMIDITY: | 10% to 90%, RHL non-condensing. |
| POWER CONSUMPTION: | 100–240V AC, 50/60Hz, 135VA. |
| DIMENSIONS: | 19" x 14.2" x 4U (W, D, H) rack-mountable. |
| WEIGHT: | 8.1kg (17.9lbs) approx. |
| ACCESSORIES: | Power cord, infrared remote control transmitter. |

CONFIGURATIONS

Input Modules

| | |
|---------------|--|
| DVI-IN2-F16 | 2-Input DVI Card (F-16) |
| HDCP-IN2-F16 | 2-Input DVI (HDCP) Card (F-16) |
| DL-IN1-F16 | 1-Input DVI Dual Link Card (F-16) |
| F610-IN2-F16 | 2-Input DVI over 4LC Fiber Card (F-16) |
| H-IN2-F16 | 2-Input HDMI Card (F-16) |
| DGKat-IN2-F16 | 2-Input HDMI & RS-232 over DGKat Card (F-16) |
| HDBT-IN2-F16 | 2-Input HDMI over HDBaseT Card (F-16) |
| F670-IN2-F16 | 2-Input HDMI over OM3 Fiber Card (F-16) |

Output Modules

| | |
|----------------|---|
| DVI-OUT2-F16 | 2-Output DVI Card (F-16) |
| HDCP-OUT2-F16 | 2-Output DVI (HDCP) Card (F-16) |
| DL-OUT1-F16 | 1-Output DVI Dual Link Card (F-16) |
| F610-OUT2-F16 | 2-Output DVI over 4LC Fiber Card (F-16) |
| H-OUT2-F16 | 2-Output HDMI Card (F-16) |
| DGKat-OUT2-F16 | 2-Output HDMI & RS-232 Input over DGKat Card (F-16) |
| HDBT-OUT2-F16 | 2-Output HDMI over HDBaseT Card (F-16) |
| F670-OUT2-F16 | 2-Output HDMI over OM3 Fiber Card (F-16) |

Module Plate

| | |
|---------|--|
| BLP-F16 | Blank Cover Plate for Empty Module Slots |
|---------|--|