



KRAMER

WP-211T

4K60 4:2:0 HDCP 2.2 HDMI WallPlate Auto
Switcher and PoE Acceptor over HDBaseT

| HDMI | Ethernet - RJ-45 | 4K/60 UHD (4:2:0)
| HDCP 2.2 Compatible



WP211T is a highperformance wallplate automatic switcher for 4K, HDBaseT, HDMI 1.4, HDCP 2.2 video signals. Offering priority and lastconnected switching options, it automatically switches according to the selected switching scheme based on active video signal detection. WP211T can be powered through PoE over the HDBaseT connection

FEATURES

- Max. Data Rate - 8.91Gbps (2.97Gbps per data channel)
- Max. Resolution - 4K@60Hz (4:2:0)
- HDMI 1.4 & HDCP 2.2 Compliant
- Supports up to 40m reach at 4K@60Hz (4:2:0)
- PoE Acceptor
- Kramer Equalization and re-Klocking Technology
- HDTV Compatible
- 3D Pass-Though



KRAMER

TECHNICAL SPECIFICATIONS

2 HDMI	On female HDMI connectors
1 HDBaseT	On an RJ45 connector
Max. Data Rate	8.91Gbps (2.97Gbps per graphic channel)
Max. Resolution	4K@60Hz (4:2:0)
Standards Compliance	HDCP 2.2 (does not support conversion to HDCP 1.4), HDMI 1.4
Controls	Last connected/priority DIPswitches and toggles to select the input manually
REGULATORY COMPLIANCE	EMC EN 55032;IEC 609501(ed.2);IEC 609501(ed.2)am1;IEC 609501(ed.2)am2
Operating Temperature	0° to +40°C (32° to 104°F)
Storage Temperature	40° to +70°C (40° to 158°F)
Humidity	10% to 90%, RHL noncondensing
Source	5V DC
Consumption	400mA
Included	5V DC 4A desktop power adapter



KRAMER

CONFIGURATIONS

WP-211T/US(W)	HDMI WallPlate Auto Switcher and PoE Acceptor over HDBaseT - White
WP-211T/US(B)	HDMI WallPlate Auto Switcher and PoE Acceptor over HDBaseT - Black
WP-211T/EU(W)	HDMI WallPlate Auto Switcher and PoE Acceptor over HDBaseT - White
WP-211T/EU(B)	HDMI WallPlate Auto Switcher and PoE Acceptor over HDBaseT - Black

